

STANDARD







APPLICATIONS

The CLL-EXTCMB series combines LED exit illumination with relible LED emergency lamp heads capable of lighting egress for minimum of 90 min. This attractive low-profile design offers maintenance-free, long life, dependable service. The universal mount covers a wide range of applications such as above doors and areas with restricted space.

FEATURES

- * Long lasting, efficient ultra bright white LED lamp heads
- * 24 SMD 2825 LED per head
- * High performance chrome-plated metallized reflector and plastic lens for optimal light distribution
- * Adjustable LED lamp heads provides optimal center-to-center spacing
- * Long life, energy efficient Red LED EXIT sign illumination
- * Dual 120/277 voltage
- * Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- * 9.6V 700 mAH long life, maintenance-free, rechargeable NiCd battery
- * Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- * Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours

ORDERING INFORMATION




WARRANTY / LISTING

- * Five year warranty on all electronics and housing. Two year warranty on battery
- * Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- * UL Listed for damp locations (32°F 122°C)

MOUNTING

- * Universal J-box mounting pattern
- * Universal knockout pattern on back plate for wall mount

DIMENSIONS



HOUSING

* Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white finish

PART#	No of faces		Letter Color		Housing Color		Remote capable
CLL-EXTCMB-RED	1	Universal Single	R	Red	W	White	
DTH-EXTCMB-GRN	1	Universal Single	G	Green	W	White	
DTH-EXTCMB-RED/BLK	1	Universal Single	R	Red	В	Black	
CLL-EXTCMB-RC	1	Universal Single	R	Red	W	White	RC : Remote Capable up to 3W